













# **Description**

An alkali resistant glass fibre woven mesh, ideal for the reinforcement of render or basecoat plaster. An ideal anti-crack reinforcement for rendering sytems. It is also widely used on external wall insulation systems, roof tiles and carpets.

Offering incredible strength when embedded into wet base coat renders and is light, economical, tear resistant and easy to use. Stabilises surfaces and prevents cracking.

Can also be used:

- as a reinforcement of waterproof membranes, felts and similar rooving materials.
- in conjunction with tile adhesives to distribute stress with ceramic, marble and stone tiles.
- With floor coverings to maintain stability and durability.

# **Application**

Apply an even background coat of render to the required thickness. Place the mesh into the wet render and lightly press in with a trowel to completely cover the mesh. Overlap joints in the mesh by a minimum of 5cm. Trowel over to give the required finish effect. Re-inforcement for waterproof membranes, felts and similar roofing materials. Distributes stress evenly when used with marble, stone and ceramic tiles. Maintains stability and durability when used with floorcoverings.

# Coverage

1 roll will cover 50m of substrate at a 1m width.

### **Storage Conditions**

Store in dry conditions

## **Disposal of Containers**

Do not leave empty bags or packaging where they could be harmful to children, animals or the environment. Remove any bags or material to a central disposal point in accordance with local regulations.

## **Health & Safety**

Low hazardous product. Keep out of reach of children. Safety data sheet available for professional user on request, or can be downloaded from www.bond-it.co.uk.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

# **Specification Summary**

| Colour       | Pink                  |
|--------------|-----------------------|
| Composition  | Glass fibre strands   |
| Weight       | 160gsm                |
| Size         | 50m length x 1m width |
| Construction | 4x4mm mesh            |


### **Container Sizes**

| Code:    | BDRENM        |
|----------|---------------|
| Size:    | 50M x 1M      |
| Barcode: | 5060021371386 |









Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310 Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



