

# LOW ODOUR WOODWORM KILLER

Larsen Low Odour Woodworm Killer is a ready to use treatment for the eradication of all types and life stages of wood boring insects and their larvae, including the common furniture beetle and the house longhorn beetle. It's low odour microemulsion technology penetrates deeply into the wood to actively kill and protect against re-infestation. Woodworm Killer can be used on most internal furniture, woodwork and joinery such as doors, window frames, roof timbers, floorboards, joists, rafters, etc. It can be over painted, stained, varnished, or polished when dry if required.

**KILLS WOOD DESTROYING INSECTS**  
**PREVENTS REINFESTATION**  
**DEEP PENETRATING**  
**MICROEMULSION TECHNOLOGY**  
**LOW ODOUR**



**TECHNICAL INFORMATION**

<b>PRODUCT INFORMATION</b>	
<b>FORM:</b>	Milky Liquid
<b>COLOUR:</b>	Dries Clear
<b>FLASH POINT:</b>	N/A Non flammable
<b>HAZARD INFORMATION:</b>	Causes serious eye irritation. Very toxic to aquatic life with long lasting effects.
<b>CLEANING:</b>	Clean tools, equipment, etc. using warm water.
<b>PACKAGING:</b>	1L, 5L
<b>STORAGE CONDITIONS:</b>	Store in sealed containers in dry conditions, protect from frost and store below 40°C. Store in a safe place away from food or feed stuffs.
<b>SHELF LIFE:</b>	Minimum 24 months in unopened manufacturer's packaging
<b>APPLICATION INFORMATION</b>	
<b>ACTIVE</b>	CONTAINS Permethrin 2.5g/L
<b>BS EN 335 USE CLASS :</b>	UC2
<b>APPLICATION RATE:</b>	<b>200-300ml/m<sup>2</sup></b> Curative - 1L per 3.3m <sup>2</sup> Preventative – 1L per 5m <sup>2</sup>
<b>APPLICATION METHOD:</b>	Low pressure spray or brush
<b>APPLICATION TEMPERATURE:</b>	+5°C to +30°C
<b>DRYING TIME:</b>	1 hr
<b>OVERCOAT:</b>	24 hrs
<b>UK AUTHORISATION</b>	HSE 10138
<b>ROI AUTHORISATION</b>	PCS 98336

## DIRECTIONS FOR USE

### PREPARATION

Wood should be clean and free from wood dust, paint, varnish and other contaminants which may prevent penetration.

### APPLICATION

Apply by low pressure spray or brush at a rate of 200-300ml/m<sup>2</sup> depending on application.

As eradicant insecticide - Apply at 300ml/m<sup>2</sup>(1L per 3.3m<sup>2</sup>)

As a preventative insecticide - Apply at 200ml/m<sup>2</sup>(1L per 5m<sup>2</sup>)

Product is touch dry in 1 hour depending on wood and ambient conditions.

Unprotected persons and animals should be kept away from treated areas for 48 hours or until dry.

Wood can be over coated after 24hrs if dry.

### RESTRICTIONS

FOR USE ONLY AS A WOOD PRESERVATIVE.

Apply by brush or low pressure spray. Apply at a rate of 200-300ml/m<sup>2</sup>. Users must comply in full with all their legal responsibilities under The Control of Pesticide Regulations 1986 (as amended), including complying with all conditions of approval. This product is approved under The Control of Pesticides Regulations 1986 (as amended) for use as directed.

READ ALL PRECAUTIONS BEFORE USE

This material and its container must be disposed of in a safe way. Do not contaminate foodstuffs, eating utensils or food contact surfaces. Cover all water storage tanks before application. This material and its container must be disposed of in a safe way. Do not touch treated surfaces until dry. Hazardous to bees. Do not use on beehives or beekeeping equipment. Wash hands and exposed skin before meals and after use. Keep in a safe place.

### QUALITY

This product is manufactured in a plant controlled under an integrated management system third party certified to BS EN ISO 9001.