

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Trade name : 46A - Tixotrope Contact Adhesive

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Intended for general public  
Main use category : Consumer use, Professional use  
Use of the substance/mixture : Adhesives, binding agents

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****Supplier**

Soudal N.V.  
Everdongenlaan 18-20  
2300 Turnhout  
Belgium  
T +32 14 42 42 31 - F +32 14 42 65 14  
[sds@soudal.com](mailto:sds@soudal.com) - [www.Soudal.com](http://www.Soudal.com)

**1.4. Emergency telephone number**

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2 H225  
Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 2 H319  
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336  
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411  
Full text of H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: ethyl acetate; acetone; hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; cyclohexane

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 - Avoid breathing vapours, mist.

P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P391 - Collect spillage.

P405 - Store locked up.

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH208 - Contains N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide). May produce an allergic reaction.

Extra phrases

: This product is not to be used under conditions of poor ventilation.  
This product is not to be used for carpet laying.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
ethyl acetate (141-78-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
cyclohexane (110-82-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
butanone (78-93-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
zinc oxide (1314-13-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2,6-di-tert-butyl-p-cresol (128-37-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC-No.: 921-024-6 REACH-no: 01-2119475514-35	≥ 10 – < 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411
ethyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	≥ 10 – < 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
cyclohexane substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 110-82-7 EC-No.: 203-806-2 EC Index-No.: 601-017-00-1 REACH-no: 01-2119463273-41	≥ 10 – < 25	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
acetone substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	≥ 10 – < 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
butanone substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 REACH-no: 01-2119457290-43	≥ 10 – < 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
4-tert-butylphenol-formaldehyde copolymer	CAS-No.: 25085-50-1 EC-No.: 472-160-3	≥ 5 – < 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1- amide)	CAS-No.: 123-26-2 EC-No.: 204-613-6 REACH-no: 01-2119978265-26	≥ 0,1 – < 1	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
2,6-di-tert-butyl-p-cresol substance with national workplace exposure limit(s) (BE)	CAS-No.: 128-37-0 EC-No.: 204-881-4 REACH-no: 01-2119555270-46	≥ 0,1 – < 1	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 (M=1)
zinc oxide substance with national workplace exposure limit(s) (BE)	CAS-No.: 1314-13-2 EC-No.: 215-222-5 EC Index-No.: 030-013-00-7 REACH-no: 01-2119463881-32	≥ 0,1 – < 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, mist. Avoid contact with skin and eyes.
----------------------	--

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Absorb spilled material with sand or earth.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Ensure adequate ventilation.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, mist. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

##### ethyl acetate (141-78-6)

##### EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Ethyl acetate
IOEL TWA	734 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
IOEL STEL	1468 mg/m <sup>3</sup>
IOEL STEL [ppm]	400 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164 COMMISSION DIRECTIVE (EU) 2017/164

##### Belgium - Occupational Exposure Limits

Local name	Acétate d'éthyle # Ethylacetaat
OEL TWA	734 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021

##### acetone (67-64-1)

##### EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Acetone
IOEL TWA	1210 mg/m <sup>3</sup>
IOEL TWA [ppm]	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>acetone (67-64-1)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Acétone # Aceton
OEL TWA	1210 mg/m <sup>3</sup> 594 mg/m <sup>3</sup>
OEL TWA [ppm]	500 ppm 246 ppm
OEL STEL	2420 mg/m <sup>3</sup> 1187 mg/m <sup>3</sup>
OEL STEL [ppm]	1000 ppm 492 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
<b>cyclohexane (110-82-7)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Cyclohexane
IOEL TWA	700 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Cyclohexane # Cyclohexaan
OEL TWA	350 mg/m <sup>3</sup>
OEL TWA [ppm]	100 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
<b>butanone (78-93-3)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Butanone
IOEL TWA	600 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
IOEL STEL	900 mg/m <sup>3</sup>
IOEL STEL [ppm]	300 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Belgium - Occupational Exposure Limits</b>	
Local name	2-Butanone # 2-Butanon
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
<b>zinc oxide (1314-13-2)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Zinc (oxyde de) (fraction alvéolaire) # Zinkoxide (inadembare fractie)

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

zinc oxide (1314-13-2)	
OEL TWA	2 mg/m <sup>3</sup>
OEL STEL	10 mg/m <sup>3</sup>
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021

2,6-di-tert-butyl-p-cresol (128-37-0)	
Belgium - Occupational Exposure Limits	
Local name	2,6-Di-tert-butyl-p-crésol (vapeur et aérosol) # Di-tert-butyl-4-méthylfenol (damp en aérosol)
OEL TWA	2 mg/m <sup>3</sup>
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

ethyl acetate (141-78-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1468 mg/m <sup>3</sup>
Acute - local effects, inhalation	1468 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	63 mg/kg bw/day
Long-term - systemic effects, inhalation	734 mg/m <sup>3</sup>
Long-term - local effects, inhalation	734 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	734 mg/m <sup>3</sup>
Acute - local effects, inhalation	734 mg/m <sup>3</sup>
Long-term - systemic effects, oral	4,5 mg/kg bw/day
Long-term - systemic effects, inhalation	367 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	37 mg/kg bw/day
Long-term - local effects, inhalation	367 mg/m <sup>3</sup>
PNEC (Water)	
PNEC aqua (freshwater)	0,24 mg/l
PNEC aqua (marine water)	0,024 mg/l
PNEC aqua (intermittent, freshwater)	1,65 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1,15 mg/kg dwt
PNEC sediment (marine water)	0,115 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,148 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0,2

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>ethyl acetate (141-78-6)</b>	
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	650 mg/l
<b>acetone (67-64-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	2420 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	186 mg/kg bw/day
Long-term - systemic effects, inhalation	1210 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	62 mg/kg bw/day
Long-term - systemic effects, inhalation	200 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	62 mg/kg bw/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	10,6 mg/l
PNEC aqua (marine water)	1,06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	30,4 mg/kg dwt
PNEC sediment (marine water)	3,04 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	29,5 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l
<b>hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2035 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	699 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	608 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day
<b>cyclohexane (110-82-7)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	1400 mg/m <sup>3</sup>
Acute - local effects, inhalation	1400 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	2016 mg/kg bw/day
Long-term - systemic effects, inhalation	700 mg/m <sup>3</sup>
Long-term - local effects, inhalation	700 mg/m <sup>3</sup>



# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cyclohexane (110-82-7)	
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	412 mg/m <sup>3</sup>
Acute - local effects, inhalation	412 mg/m <sup>3</sup>
Long-term - systemic effects, oral	59,4 mg/kg bw/day
Long-term - systemic effects, inhalation	206 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	1186 mg/kg bw/day
Long-term - local effects, inhalation	206 mg/m <sup>3</sup>
PNEC (Water)	
PNEC aqua (freshwater)	44,7 µg/l
PNEC aqua (marine water)	4,47 µg/l
PNEC aqua (intermittent, freshwater)	0,207 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	3,6 mg/kg dwt
PNEC sediment (marine water)	0,36 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,694 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	3,24 mg/l
butanone (78-93-3)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	1161 mg/kg bw/day
Long-term - systemic effects, inhalation	600 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	31 mg/kg bw/day
Long-term - systemic effects, inhalation	106 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	412 mg/kg bw/day
PNEC (Water)	
PNEC aqua (freshwater)	55,8 mg/l
PNEC aqua (marine water)	55,8 mg/l
PNEC aqua (intermittent, freshwater)	55,8 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	284,74 mg/kg dwt
PNEC sediment (marine water)	284,7 mg/kg dwt
PNEC (Soil)	
PNEC soil	22,5 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	1000 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	709 mg/l

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### zinc oxide (1314-13-2)

#### DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	83 mg/kg bw/day
Long-term - systemic effects, inhalation	5 mg/m <sup>3</sup>
Long-term - local effects, inhalation	0,5 mg/m <sup>3</sup>

#### DNEL/DMEL (General population)

Long-term - systemic effects, oral	0,83 mg/kg bw/day
Long-term - systemic effects, inhalation	2,5 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	83 mg/kg bw/day

#### PNEC (Water)

PNEC aqua (freshwater)	20,6 µg/l
PNEC aqua (marine water)	6,1 µg/l

#### PNEC (Sediment)

PNEC sediment (freshwater)	117,8 mg/kg dwt
PNEC sediment (marine water)	56,5 mg/kg dwt

#### PNEC (Soil)

PNEC soil	35,6 mg/kg dwt
-----------	----------------

#### PNEC (STP)

PNEC sewage treatment plant	100 µg/l
-----------------------------	----------

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

###### Eye protection:

Safety glasses (EN 166)

##### 8.2.2.2. Skin protection

###### Skin and body protection:

Protective clothing (EN 14605 or EN 13034)

###### Hand protection:

Protective gloves against chemicals (EN 374)

##### 8.2.2.3. Respiratory protection

###### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: Pasty.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: > 60 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 23 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: ≈ 1149,4 mm <sup>2</sup> /s (20°C)
Viscosity, dynamic	: ≈ 1000 Pa·s (20°C)
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 73 – 76 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### ethyl acetate (141-78-6)

LD50 oral rat	10200 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 20000 mg/kg bodyweight (24 hour cuff method, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))

#### acetone (67-64-1)

LD50 oral rat	5800 mg/kg (Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	76 mg/l (4 h, Rat, Female, Weight of evidence, Inhalation (vapours))

#### hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat	> 25,2 mg/l air Animal: rat

#### cyclohexane (110-82-7)

LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 19,07 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

#### butanone (78-93-3)

LD50 oral rat	2193 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 8100 mg/kg bw/day (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))

#### zinc oxide (1314-13-2)

LD50 oral rat	> 5000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5,7 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (dust), 14 day(s))

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>2,6-di-tert-butyl-p-cresol (128-37-0)</b>	
LD50 oral rat	> 6000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
<b>N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) (123-26-2)</b>	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Read-across, Oral)
LC50 Inhalation - Rat	> 5,05 mg/l air (OECD 436: Acute inhalation toxicity-acute toxic class method, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol))
Skin corrosion/irritation	: Causes skin irritation.
<b>ethyl acetate (141-78-6)</b>	
pH	No data available in the literature
<b>acetone (67-64-1)</b>	
pH	5 – 6 (20 °C)
<b>cyclohexane (110-82-7)</b>	
pH	7 (5.2E-3 %, 24 °C)
<b>butanone (78-93-3)</b>	
pH	No data available in the literature
<b>zinc oxide (1314-13-2)</b>	
pH	6,07 – 6,55 (2.9E-4 %, 20 °C, OECD 105: Water Solubility)
<b>2,6-di-tert-butyl-p-cresol (128-37-0)</b>	
pH	No data available in the literature
Serious eye damage/irritation	: Causes serious eye irritation.
<b>ethyl acetate (141-78-6)</b>	
pH	No data available in the literature
<b>acetone (67-64-1)</b>	
pH	5 – 6 (20 °C)
<b>cyclohexane (110-82-7)</b>	
pH	7 (5.2E-3 %, 24 °C)
<b>butanone (78-93-3)</b>	
pH	No data available in the literature
<b>zinc oxide (1314-13-2)</b>	
pH	6,07 – 6,55 (2.9E-4 %, 20 °C, OECD 105: Water Solubility)
<b>2,6-di-tert-butyl-p-cresol (128-37-0)</b>	
pH	No data available in the literature
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>2,6-di-tert-butyl-p-cresol (128-37-0)</b>	
NOAEL (chronic, oral, animal/male, 2 years)	25 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Effect type: toxicity (migrated information)
Reproductive toxicity	: Not classified
<b>acetone (67-64-1)</b>	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
<b>ethyl acetate (141-78-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>acetone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>cyclohexane (110-82-7)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>butanone (78-93-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>4-tert-butylphenol-formaldehyde copolymer (25085-50-1)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
<b>ethyl acetate (141-78-6)</b>	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
<b>zinc oxide (1314-13-2)</b>	
LOAEL (dermal, rat/rabbit, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (oral, rat, 90 days)	31,52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
<b>2,6-di-tert-butyl-p-cresol (128-37-0)</b>	
LOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Animal sex: male
NOAEL (oral, rat, 90 days)	25 mg/kg bodyweight Animal: rat, Animal sex: male
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
<b>46A - Tixotrope Contact Adhesive</b>	
Viscosity, kinematic	≈ 1149,4 mm²/s (20°C)
<b>ethyl acetate (141-78-6)</b>	
Viscosity, kinematic	No data available in the literature

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>acetone (67-64-1)</b>	
Viscosity, kinematic	No data available in the literature
<b>hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
Viscosity, kinematic	0,61 mm²/s
<b>cyclohexane (110-82-7)</b>	
Viscosity, kinematic	0 mm²/s (26 °C)
<b>butanone (78-93-3)</b>	
Viscosity, kinematic	No data available in the literature
<b>zinc oxide (1314-13-2)</b>	
Viscosity, kinematic	Not applicable (solid)
<b>2,6-di-tert-butyl-p-cresol (128-37-0)</b>	
Viscosity, kinematic	3,47 mm²/s (0 °C, ASTM D445: Capillary viscometer)

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.  
Not rapidly degradable

<b>ethyl acetate (141-78-6)</b>	
LC50 - Fish [1]	230 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
NOEC (chronic)	2,4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>acetone (67-64-1)</b>	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>cyclohexane (110-82-7)</b>	
LC50 - Fish [1]	4,53 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
EC50 - Crustacea [1]	0,9 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cyclohexane (110-82-7)	
EC50 72h - Algae [1]	3,4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	9,317 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
butanone (78-93-3)	
LC50 - Fish [1]	2993 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	308 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
zinc oxide (1314-13-2)	
LC50 - Fish [1]	1,55 mg/l (96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Zinc ion)
2,6-di-tert-butyl-p-cresol (128-37-0)	
LC50 - Fish [1]	0,199 mg/l (ECOSAR v1.00, 96 h, Pisces, QSAR, Lethal)
EC50 - Crustacea [1]	0,48 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [1]	> 0,24 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,023 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0,053 mg/l Test organisms (species): Oryzias latipes Duration: '42 d'
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) (123-26-2)	
EC50 72h - Algae [1]	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)

## 12.2. Persistence and degradability

ethyl acetate (141-78-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0,293 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1,69 g O <sub>2</sub> /g substance
ThOD	1,82 g O <sub>2</sub> /g substance
acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1,43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1,92 g O <sub>2</sub> /g substance



# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>acetone (67-64-1)</b>	
ThOD	2,2 g O <sub>2</sub> /g substance
<b>cyclohexane (110-82-7)</b>	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0,22 g O <sub>2</sub> /g substance
ThOD	3,425 g O <sub>2</sub> /g substance
<b>butanone (78-93-3)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2,03 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2,31 g O <sub>2</sub> /g substance
ThOD	2,44 g O <sub>2</sub> /g substance
<b>zinc oxide (1314-13-2)</b>	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
<b>2,6-di-tert-butyl-p-cresol (128-37-0)</b>	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	0,51 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2,27 g O <sub>2</sub> /g substance
ThOD	2,977 g O <sub>2</sub> /g substance
<b>N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) (123-26-2)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>12.3. Bioaccumulative potential</b>	
<b>ethyl acetate (141-78-6)</b>	
BCF - Fish [1]	30 (3 day(s), Leuciscus idus, Static renewal, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	0,68 (Experimental value, EPA OPPTS 830.7560, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>acetone (67-64-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	-0,23 (Test data)
Bioaccumulative potential	Not bioaccumulative.
<b>hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
Partition coefficient n-octanol/water (Log Pow)	3,4 – 5,2
<b>cyclohexane (110-82-7)</b>	
BCF - Fish [1]	167 l/kg (Pimephales promelas, QSAR, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3,44 (Experimental value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>butanone (78-93-3)</b>	
Partition coefficient n-octanol/water (Log Pow)	0,3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>zinc oxide (1314-13-2)</b>	
BCF - Fish [1]	78 – 2060 (14 day(s), Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	1,53 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.
<b>2,6-di-tert-butyl-p-cresol (128-37-0)</b>	
Partition coefficient n-octanol/water (Log Pow)	4,17 (Experimental value, 37 °C)
Bioaccumulative potential	Potential for bioaccumulation ( $4 \leq \text{Log Kow} \leq 5$ ).
<b>N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) (123-26-2)</b>	
Partition coefficient n-octanol/water (Log Pow)	$\geq 5,86$ (Read-across, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
<b>12.4. Mobility in soil</b>	
<b>ethyl acetate (141-78-6)</b>	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.
<b>acetone (67-64-1)</b>	
Surface tension	23,3 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0,374 – 0,988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
<b>cyclohexane (110-82-7)</b>	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2,89 (log Koc, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
<b>butanone (78-93-3)</b>	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0,654 – 1,281 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.
<b>zinc oxide (1314-13-2)</b>	
Surface tension	Not applicable (solid)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2,2 (log Koc, Literature study)
Ecology - soil	Low potential for adsorption in soil.

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2,6-di-tert-butyl-p-cresol (128-37-0)

Surface tension	Not applicable (water solubility < 1 mg/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4,362 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Ecology - soil	Low potential for mobility in soil. May be harmful to plant growth, blooming and fruit formation.

### N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) (123-26-2)

Surface tension	32,7 mN/m (20 °C, 0.1 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≥ 5,63 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Read-across, GLP)
Ecology - soil	Low potential for mobility in soil.

## 12.5. Results of PBT and vPvB assessment

### Component

ethyl acetate (141-78-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
cyclohexane (110-82-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
butanone (78-93-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
zinc oxide (1314-13-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2,6-di-tert-butyl-p-cresol (128-37-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

## 12.6. Endocrine disrupting properties

No additional information available

## 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Collect all waste in suitable and labelled containers and dispose according to local legislation.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable. Flammable vapours may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1133	UN 1133	UN 1133	UN 1133	UN 1133
<b>14.2. UN proper shipping name</b>				
ADHESIVES	ADHESIVES	Adhesives	ADHESIVES	ADHESIVES
<b>Transport document description</b>				
UN 1133 ADHESIVES, 3, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 1133 ADHESIVES, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS (23°C c.c.)	UN 1133 Adhesives, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

### 14.6. Special precautions for user

Special transport precautions : ADHESIVES containing flammable liquid (having a flash-point below 23 °C and viscous according to 2.2.3.1.4) (vapour pressure at 50 °C not more than 110 kPa)

#### Overland transport

Classification code (ADR) : F1  
Limited quantities (ADR) : 5I  
Excepted quantities (ADR) : E1  
Packing instructions (ADR) : P001, IBC02, R001  
Special packing provisions (ADR) : PP1, BB4  
Mixed packing provisions (ADR) : MP19  
Transport category (ADR) : 3  
Special provisions for carriage - Operation (ADR) : S2  
Tunnel restriction code (ADR) : E

#### Transport by sea

Special provisions (IMDG) : 223, 955  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T2  
Tank special provisions (IMDG) : TP1

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

### Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC02, R001
Special packing provisions (RID)	: PP1, BB4
Mixed packing provisions (RID)	: MP19
Transport category (RID)	: 3
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 33

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Other information, restriction and prohibition regulations	: This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. More information: <a href="https://ec.europa.eu">https://ec.europa.eu</a> .
--	---

#### REACH Annex XVII (Restriction List)

##### EU restriction list (REACH Annex XVII)

Reference code	Applicable on	Entry title or description
3(a)	46A - Tixotrope Contact Adhesive ; ethyl acetate ; acetone ; hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ; cyclohexane ; butanone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	46A - Tixotrope Contact Adhesive ; ethyl acetate ; acetone ; hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ; cyclohexane ; butanone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	46A - Tixotrope Contact Adhesive ; hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ; cyclohexane	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
57.	cyclohexane	Cyclohexane

### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### VOC Directive (2004/42)

VOC content : 73 – 76 %

### Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see [https://ec.europa.eu/home-affairs/system/files/2021-11/list\\_of\\_competent\\_authorities\\_and\\_national\\_contact\\_points\\_en.pdf](https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf)

### Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 16: Other information

#### Indication of changes

Section	Changed item	Change	Comments
2.2	Additional information	Added	EUH208

#### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative

# 46A - Tixotrope Contact Adhesive

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Abbreviations and acronyms:

ED	Endocrine disrupting properties
----	---------------------------------

### Full text of H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide). May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 2	H225	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 2	H411	Calculation method

Safety Data Sheet (SDS), EU-2022-2

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.