

TECHNICAL DATA SHEET NO: P12 VERSION: 1-2/2/09 PAGE: 1 OF 2 DATE OF ISSUE: 7/16/2013

# **EVERBUILD P12 CENTRAL HEATING NOICE SILENCER**



Colour	Product Code	Pack Size	Box Qty
-	P12NOISE1	1ltr	12

# **Product Description**

Formerly SCALEX by Purimachos

EVERBUILD P12 NOISE SILENCER is a non-acid based de-scaler which stays permanently in the system with no need to drain or flush. P12 NOISE SILENCER helps to prevent knocking and kettling caused by lime scale and sludge build up.

#### **Benefits**

- Removes scale and baked on sludge deposits.
- Prevents scale from reforming.
- Compatible with all EVERBUILD central heating products.
- Restores heating efficiency to extend the life of the boiler.

# Areas for Use

- New and existing central heating systems.
- Extensions to existing systems.

## Limitations

- Use only as directed.
- Only suitable for fully indirect systems.
- Not suitable for use in PRIMATIC single feed cylinders.
- Central heating systems should be protected with P14 SYSTEM INHIBITOR.

## **Application**

For best results pre-treat with P11 SYSTEM CLEANSER prior to adding P12 NOISE SILENCER. Add P14 SYSTEM INHIBITOR to protect the metallic components in the system.

- 1) Locate the central heating feed and expansion tank.
- 2) Shake the bottle and pour contents into the tank.
- 3) P12 is gradually drawn into the system and provides full effect within 1-6 weeks.
- 4) Bleed radiators after 2-3 days and again after 2-3 weeks.



TECHNICAL DATA SHEET NO: P12 VERSION: 1-2/2/09
PAGE: 2 OF 2 DATE OF ISSUE: 7/16/2013

#### **Health & Safety**

Consult COSHH data sheet for full list of hazards.

## **Storage**

Store in original container away from frost in a dry area.

#### Coverage

1ltr treats 100ltr system capacity

## **Shelf Life**

36 months in original unopened containers.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guaran tee applies within the context of the statutory regulations and provisions in force, current professional standards and in accord ance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.