

	Zeroflame Treatment	Zeroflame Paint	Zeroflame AquaSteel WB+
INTERIOR SUBSTRATES			
Bare Plaster, Brick, Masonry, etc	x	✓	x
Previously Painted Plaster, Brick, Masonry, etc	x	✓	x
Solid Bare Timber	✓	✓	x
Previously Painted Timber & MDF/Plywood	x	✓	x
Steel Members	x	x	✓
Achieves European Class B-s2,d0 (equivalent to Class 0 & 1) Tested to European Standard EN13501-1	✓	✓	x
30 mins & 60 mins Protection Fire tested to BS476: Part 21:1987	x	x	✓
EXTERIOR SUBSTRATES			
Masonry	x	x	x
Solid Bare Timber	✓	x	x
Previously Painted Timber	x	x	x
Steel	x	x	x

NOTES:

Zeroflame Treatment

- Clear impregnation treatment for bare timber
- Waterborne, virtually odourless
- Single pack
- Coverage rate: 4m²/L
- Can be overcoated with water based non-flammable coatings
- Fully certified

Zeroflame Paint

- Single pack, dries to a matt white finish
- Can be overcoated with up to 3 coats of water based non-flammable coatings
- Coverage rate: 3.7m²/L
- Fully certified

Zeroflame AquaSteel WB+

- Water based, single pack coating which dries to a matt white finish and can be overcoated with Zeroflame AquaSteel WB+ Finish if a decorative finish is required
- Steel must be primed with red oxide or zinc phosphate primer before applying Zeroflame AquaSteel WB+
- Fully certified
- Available in 2.5L, 5L & 10L