OWATROL TEXTROL - TEXT01HCS

Date: 12/08/2016 Page 1/10

Revision: N°1 (28/07/2016)

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: OWATROL TEXTROL

Product code: TEXT01HCS.

(All tones)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint and varnish

1.3. Details of the supplier of the safety data sheet

Registered company name: DURIEU S.A..

Address: Z.I. "La Marinière" 2 bis, rue Charles de Gaulle.91070.BONDOUFLE.FRANCE.

Telephone: +33 (0)1.60.86.48.70. Fax: +33 (0)1.60.86.84.84.

info@durieu.com www.durieu.com

1.4. Emergency telephone number: + 33 (0)1.45.42.59.59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

HCS compliant.

Skin sensitisation, Category 1 (Skin Sens. 1).

2.2. Label elements

Mixture for spray application.

HCS compliant.

Hazard pictograms:



GHS07

Signal Word : WARNING

Product identifiers:

CAS 55406-53-6 3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC)

Hazard statements:

H317 May cause an allergic skin reaction.

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P260 Do not breathe dust vapours.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards

No data available.

OWATROL TEXTROL - TEXT01HCS

Date: 12/08/2016 Page 2/10

Revision: N°1 (28/07/2016)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

Identification	HCS	Nota	%
INDEX: PCP186	GHS08		25 <= x % < 50
EC: 918-481-9	Dgr		
REACH: 01-2119457273-39	Flam. Liq. 4, H227		
	Asp. Tox. 1, H304		
HYDROCARBONS, C10-C13, N-ALKANES,			
ISOALKANES, CYCLICS, <2% AROMATICS			
INDEX: 298	GHS07, GHS08		$2.5 \le x \% < 10$
EC: 918-811-1	Dgr		
REACH: 01-2119463583-34	Flam. Liq. 4, H227		
	Asp. Tox. 1, H304		
HYDROCARBONS, C10, AROMATICS, <1%	Acute Tox. 5, H313		
NAPHTALENE	Acute Tox. 5, H333		
	STOT SE 3, H336		
INDEX: 061	GHS07, GHS05		$0 \le x \% < 1$
CAS: 55406-53-6	Dgr		
EC: 259-627-5	Acute Tox. 4, H302		
	Acute Tox. 5, H313		
3-IODO-2-PROPYNYL BUTYLCARBAMATE	Skin Sens. 1, H317		
(IPBC)	Eye Dam. 1, H318		
	Acute Tox. 4, H332		
	STOT SE 3, H335		

SECTION 4: FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

This product is not classed as flammable.

5.1. Extinguishing media

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- foam
- multipurpose ABC powder

OWATROL TEXTROL - TEXT01HCS

Date: 12/08/2016 Page 3/10

Revision: N°1 (28/07/2016)

- BC powder
- carbon dioxide (CO2)

Unsuitable methods of extinction

Direct water jet.

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Keep containers tightly closed.

Fire prevention:

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

$\label{lem:commended} \textbf{Recommended equipment and procedures:}$

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Never pour water into this mixture.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Part used containers must be properly closed and kept in upright position.

Stock between +5°C and +30°C in a dry, well ventilated place.

Keep only in the original container

OWATROL TEXTROL - TEXT01HCS

Date: 12/08/2016 Page 4/10

Revision: N°1 (28/07/2016)

Do not keep in plastic containers - may soften plastic.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

Recommended types of packaging:

- Jars
- Buckets
- Drums

Suitable packaging materials:

- Metal

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)

Recommended properties:

- Impervious gloves in accordance with standard EN374

Permeability time: >480 min for a thickness >0.45 mm

CEN recommendations: EN 420 and EN 374/3

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Type of FFP mask:

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Version: N°1 (28/07/2016)

DURIEU S.A.

OWATROL TEXTROL - TEXT01HCS

Category:

- FFP2

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

- A2 (Brown)
- B2 (Grey)

Particle filter according to standard EN143:

- P2 (White)

CEN recommendations: EN 136, EN 140, EN 405 for masks and EN 143, EN 149 for filters.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information:

Physical state : Fluid liquid.
Colour : Amber

Important health, safety and environmental information

pH: Not relevant.
Boiling point/boiling range: Not relevant.

Intervalle de point d'éclair : 60° C (140 °F) < PE <= 93°C (199,4 °F)

Explosive properties, lower explosivity limit (%):

Explosive properties, upper explosivity limit (%):

7

Vapour pressure (50°C): Not relevant.

Vapour density: >1
Density: <1
Water solubility: Insoluble.

Viscosity: v>20.5mm²/s (40°C)

Method for determining the viscosity:

ISO 3104 (Petroleum products - Transparent and opaque liquids -

Determination of kinematic viscosity and calculation of dynamic viscosity).

Date: 12/08/2016 Page 5/10

Revision: N°1 (28/07/2016)

Melting point/melting range:

Self-ignition temperature:

Not relevant.

Decomposition point/decomposition range:

Not relevant.

Not relevant.

**VOC:

**C44%

9.2. Other information

VOC (g/l): 455

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid:

- humidity

Protect from moisture. Reaction with water can cause an exothermic reaction.

Always stock in its original packaging. Do not transfer in another package.

10.5. Incompatible materials

Keep away from:

- water

Acids and oxidizing agents.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

Version: N°1 (28/07/2016)

DURIEU S.A.

OWATROL TEXTROL - TEXT01HCS

Date : 12/08/2016 Page 6/10 Revision : N°1 (28/07/2016)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity:

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6)

Oral route : LD50 = 1056 mg/kg

Species: Rat

OECD Guideline 401 (Acute Oral Toxicity)

 $Dermal \ route: \\ LD50 > 2000 \ mg/kg$

Species: Rat

OECD Guideline 402 (Acute Dermal Toxicity)

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE

Oral route: LD50 > 5000 mg/kg

Species: Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route: LD50 > 2000 mg/kg

Species : Rabbit

OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a): LC50 = 4.688 mg/l

Species : Rat

OECD Guideline 403 (Acute Inhalation Toxicity)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

 $Oral \ route: \\ LD50 > 5000 \ mg/kg$

Species: Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 5000 mg/kg

Species: Rabbit

OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a): LC50 = 4.951 mg/l

Species: Rat

OECD Guideline 403 (Acute Inhalation Toxicity)

Germ cell mutagenicity:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE

No mutagenic effect.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

No mutagenic effect.

Carcinogenicity:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE Carcinogenicity Test: Negative.

Version: N°1 (28/07/2016)

DURIEU S.A.

OWATROL TEXTROL - TEXT01HCS

No carcinogenic effect.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Carcinogenicity Test: Negative.

No carcinogenic effect.

Reproductive toxicant:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE

No toxic effect for reproduction

OECD Guideline 414 (Prenatal Developmental Toxicity Study)

Date: 12/08/2016 Page 7/10

Revision: N°1 (28/07/2016)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

No toxic effect for reproduction

OECD Guideline 414 (Prenatal Developmental Toxicity Study)

11.1.2. Mixture

SECTION 12: ECOLOGICAL INFORMATION

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

Insufficient data.

12.1.1. Substances

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE

Fish toxicity: Species: Perca fluviatilis

Crustacean toxicity: EC50 <= 10 mg/l

Species : Daphnia magna Duration of exposure : 48 h

Algae toxicity: ECr50 = 11 mg/l

Species: Pseudokirchnerella subcapitata

Duration of exposure: 72 h

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6)

Fish toxicity: LC50 = 0.067 mg/l

Species: Others

Duration of exposure: 96 h

NOEC = 0.0084 mg/l

Factor M = 1

Species : Pimephales promelas Duration of exposure : 35 days

Crustacean toxicity: EC50 = 0.16 mg/l

Species : Daphnia magna Duration of exposure : 48 h

EC50 mg/l

Species : Daphnia magna Duration of exposure : 21 days

Species: Others

Algae toxicity: ECr50 = 0.022 mg/l

Species : Scenedesmus subspicatus Duration of exposure : 72 h

NOEC = 0.0046 mg/l

Version: N°1 (28/07/2016)

DURIEU S.A.

OWATROL TEXTROL - TEXT01HCS

Factor M = 1

Species : Scenedesmus subspicatus

Date: 12/08/2016 Page 8/10

Revision: N°1 (28/07/2016)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Fish toxicity: LC50 = 1000 mg/l

Species : Oncorhynchus mykiss Duration of exposure : 96 h

Crustacean toxicity: EC50 = 1000 mg/l

Species : Daphnia magna Duration of exposure : 48 h

Algae toxicity: ECr50 = 1000 mg/l

Species: Pseudokirchnerella subcapitata

Duration of exposure: 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6) Biodegradability: Rapidly degradable.

HYDROCARBONS, C10, AROMATICS, <1% NAPHTALENE

Biodegradability: no degradability data is available, the substance is considered as not degrading

quickly.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Biodegradability: Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6)

Octanol/water partition coefficient : log Koe = 2.81

12.4. Mobility in soil

Contains volatile products that will disperse in air.

Contains a solid phase.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

The appropriate waste management of the mixture and/or its container must be determined in accordance with local regulations.

Dirty sheets can be burnt but should not be stocked nor thrown into a bin. They should be spread out and dried before. This product dries with air contact producing an exothermic reaction. Danger of auto-ignition if these precautions are not respected.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Version: N°1 (28/07/2016)

DURIEU S.A.

OWATROL TEXTROL - TEXT01HCS

Date: 12/08/2016 Page 9/10

Revision: N°1 (28/07/2016)

SECTION 14: TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

_

14.6. Special precautions for user

-

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The following regulations have been used:

- OSHA Hazard Communication Standard 29 CFR 1910.1200

- Container information:

No data available.

- Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC):

The permitted European level of VOC in this ready-to-use product is limited to 555 g/l.

The permitted European level of VOC in the ready-to-use product (category IIAf) is 700 g/l maximum (2007/2010).

- Particular provisions :

No data available.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704)

NFPA 704, Labelling: Health=2 Inflammability=2 Instability/Reactivity=1 Specific Risk=none



- Clean Water Act : Toxic Pollutants (CWA 307A)

Unlisted.

- Clean Water Act : Hazardous Substances (CWA 311)

Unlisted.

- Clean Water Act : Hazardous Substances (CWA 304b)

CAS Name

55406-53-6 3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC)

- Clean Water Act : Priority Pollutants (CWA Priority)

Unlisted.

- Clean Air Act : Hazardous Air Pollutants (CAA 112(b) HAP (188))

Unlisted.

- Clean Air Act : Organic Hazardous Air Pollutants National Emission Standards (CAA 112(b) HON (387))
Unlisted

- Clean Air Act: Protection of Stratospheric Ozone (CAA 602)

Unlisted.

- SARA 110

Unlisted.

Version: N°1 (28/07/2016)

DURIEU S.A.

OWATROL TEXTROL - TEXT01HCS

Date: 12/08/2016 Page 10/10

Revision: N°1 (28/07/2016)

- SARA 302/304

Unlisted.

- SARA 313

CAS Name

55406-53-6 3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC)

- California proposition 65: Chemicals known to the state to cause cancer or reproductive toxicity

Unlisted.

- Massachusetts: Right to Know

Unlisted.

- New Jersey : Right to Know CAS Name

55406-53-6 3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC)

- Pennsylvania: Hazardous Substance

Unlisted.

- Rhode Island : Hazardous substance list

Unlisted.

- TSCA (Toxic Substances Control Act) - USA

CAS Name

55406-53-6 3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC)

15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H227	Combustible liquid.	
H302	Harmful if swallowed.	

H302 + H332 Harmful if swallowed or if inhaled.

H304 May be fatal if swallowed and enters airways.

H313 May be harmful in contact with skin.

H313 + H333 May be harmful in contact with skin or if inhaled.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H333 May be harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

Abbreviations:

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

GHS07: Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. HCS: Hazard Communication standard (OSHA).