

Technical Data Sheet

Date of compilation: 13/08/2021

MOULD X ANTI-MOULD WALL & CEILING PAINT

DESCRIPTION

MouldX Anti-Mould wall & ceiling paint is a white, well covering, low-emission and solvent-free emission for indoor use, with protecting film against algae and fungus.

AREAS OF USE

MouldX paint is an anti-mould paint suitable for all interior surfaces at risk from mould made from plaster, concrete, gypsum boards, emulsion paint coats, etc.



SURFACE PREPARATION

The surface must be dry, firm and free of release agents (dust, oil, mould, algae, etc.). Clean areas affected by mould, moss or algae using MouldX Mould Remover chlorine free and final cleaning using clear water. Prime highly absorbent, sanding and chalking surfaces with a primer. Fill and smooth cracks, holes and unevenness using a Filler. Water-soluble contamination of the surface, which could show through when painted over with emulsion paint should be isolated using MouldX Anti-Mould stain block.

DIRECTIONS FOR USE

Apply MouldX Anti-Mould wall & ceiling paint using a paint roller, brush or an airless method. Two coats are required for optimum protection, whereby the first coat can be thinned with max. 10 % water, depending on the absorbency of the surface.

After the first coat has dried the second coat should be applied unthinned.

MouldX Anti-Mould wall & ceiling paint should not be mixed with other materials, such as dispersion and full colour systems.

Clean tools with water immediately after use.

Do not use if the surface or rooms temperature is below + 5°C.

PACKAGING, CONSUMPTION & STORAGE

Supplied in 750ml (8 units/box) / 2.5lt (1 unit/box) / 5lt (1 unit/box)

Coverage: 150-200 ml/m² per coat.

Store in a cool, but frost-free place. Keep container tightly closed.

Technical Data Sheet

Date of compilation: 13/08/2021

MOULDx ANTI-MOULd WALL & CEILING PAINT

TECHNICAL INFORMATION

Property	Value
Components	Styrene-ayrylic-dispersion, titanium dioxide, extenders, water, cellulose ether additives and additive of algicides
Density	≈ 1,6 g/cm ³
pH	≈ 8 - 9
Colour	White
Contrast ratio according to EN 13300	Class 2 by 6 m ² /l
Wet Scrub resistance according to EN 13300	Class 2

HEALTH & SAFETY

For more information and precautions for use refer to the safety data sheet.

NOTE

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Full information and advice is freely available from our Technical Services Department e-mail technical@arcbuildingproducts.ie. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.