

## Product information

# 99 14 250

## High Leverage Concreters' Nipper

High lever transmission

DIN ISO 9242



- 25 % less effort required compared to conventional concreters' nippers of the same size
- Extra-slim form for tying deep mounted steel rods
- To lace concrete reinforcing steel with binding wire from a roll
- Wire is twisted and cut in a single pass
- High-leverage joint, minimising strain, even when thick binding wires are used
- The high damping of the cutting stroke on cutting through the binding wire reduces the strain on tendons and muscles
- Cutting edges additionally hardened; cutting edge hardness approx. 61 HRC
- High-grade special tool steel, forged, multi stage oil-hardened



| General  |                       |
|--|-----------------------|
| Article No.                                    | 99 14 250             |
| EAN  | 4003773071419         |
| Pliers   | bright zinc plated    |
| Weight   | 350 g                 |
| Dimensions                                     | 250 x 47 x 25 mm      |
| Standard                                       | DIN ISO 9242          |
| REACH compliant                                | does not contain SVHC |
| RoHS compliant                                 | not applicable        |
| Technical details                              |                       |
| Cutting capacities hard wire (diameter)        | Ø 1.8 mm              |
| Cutting capacities medium hard wire (diameter) | Ø 3.3 mm              |
| Cutting edge length mm                         | 25.0 mm               |

*technical change and errors excepted*