

SAFETY DATA SHEET

ARC POT-CEM HIGH STRENGTH RAPID MORTAR

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier ARC POT-CEM HIGH STRENGTH RAPID MORTAR Product name 1.2. Relevant identified uses of the substance or mixture and uses advised against 1.3. Details of the supplier of the safety data sheet Arc Building Products Supplier **IDA Business & Technology Park** Ballynattin Arklow, Co. Wicklow Ireland Tel: +353 (0)402 32370 Fax: +353 (0)402 24168 Email: sales@Arcbuildingproducts.ie Web: www.arcbuildingproducts.ie 1.4. Emergency telephone number **Emergency telephone** +353 (0)402 32370 (Office hours only) **SECTION 2: Hazards identification** 2.1. Classification of the substance or mixture Classification (EC 1272/2008) Physical hazards Not Classified Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Not Classified **Environmental hazards** 2.2. Label elements Hazard pictograms Signal word Danger H315 Causes skin irritation. Hazard statements H318 Causes serious eye damage. H317 May cause an allergic skin reaction.

ARC POT-CEM HIGH STRENGTH RAPID MORTAR

Precautionary statements	P261 Avoid breathing dust.	
	P264 Wash contaminated skin thoroughly after handling.	
	P272 Contaminated work clothing should not be allowed out of the workplace.	
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.	
	P302+P352 IF ON SKIN: Wash with plenty of water.	
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove	
	contact lenses, if present and easy to do. Continue rinsing.	
	P310 Immediately call a POISON CENTER/ doctor.	
	P321 Specific treatment (see medical advice on this label).	
	P332+P313 If skin irritation occurs: Get medical advice/ attention.	
	P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.	
	P362+P364 Take off contaminated clothing and wash it before reuse.	
	P501 Dispose of contents/ container in accordance with national regulations.	
Contains	HIGH ALUMINA CEMENT, PORTLAND CEMENT	
2.3. Other hazards		
SECTION 3: Composition/information on ingredients		
3.1. Substances		

Classification according to EC 1272/2008 (CLP)

3.2. Mixtures

SILICA SAND		30-60%
CAS number: 14808-60-7		
Classification		
Not Classified		
HIGH ALUMINA CEMENT		10-30%
CAS number: 65997-16-2	EC number: 266-045-5	
Classification		
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
VINYL ACETATE COPOLYMER		0-1%
CAS number: —	EC number: 925-954-3	
Classification		
Not Classified		
CALCIUM SULPHATE		1-5%
CAS number: 14798-04-0		1-5 %
	EC number: 604-615-0	
Classification		
Not Classified		

ARC POT-CEM HIGH STRENGTH RAPID MORTAR

PORTLAND CEMENT	10-30%	
CAS number: 65997-15-1	EC number: 266-043-4	
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1B - H317 STOT SE 3 - H335		
The full text for all hazard state	ements is displayed in Section 16.	
SECTION 4: First aid measure	25	
4.1. Description of first aid me	asures	
General information	Risk of serious damage to eyes.	
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.	
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.	
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.	
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.	
4.2. Most important symptoms	and effects, both acute and delayed	
	te medical attention and special treatment needed	
SECTION 5: Firefighting meas	sures	
5.1. Extinguishing media		
Suitable extinguishing media	Water. Foam.	
5.2. Special hazards arising fr	om the substance or mixture	
Specific hazards	No unusual fire or explosion hazards noted.	
5.3. Advice for firefighters Protective actions during firefighting	No specific firefighting precautions known.	
SECTION 6: Accidental release	e measures	
6.1. Personal precautions, pro	tective equipment and emergency procedures	
Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.	
6.2. Environmental precaution	<u>S</u>	
Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses.	
6.3. Methods and material for containment and cleaning up		
Methods for cleaning up	Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Avoid generation and spreading of dust.	
6.4. Reference to other sections		

ARC POT-CEM HIGH STRENGTH RAPID MORTAR

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Store in closed original container at temperatures between 5°C and 30°C. This product must Storage precautions be stored in unopened bags, clear of the ground in cool dry conditions and protected from excessive drafts. If stored correctly and used within 6 months of the date shown on the bag, the activity of the reducing agent will be maintained and this product will contain, when mixed with water, no more than 0.0002% (2 ppm) soluble Chromium (VI) of the total dry weight of the cement. Shelf life in correct for sealed tubs is 6 months. Please note: the use of this product after the end of the declared storage period may increase the risk of an allergic reaction.

7.3. Specific end use(s)

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

SILICA SAND

Long-term exposure limit (8-hour TWA): 0.3 mg/m3

HIGH ALUMINA CEMENT

Long-term exposure limit (8-hour TWA): 4 mg/m³ resp.dust

VINYL ACETATE COPOLYMER

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ resp.dust

CALCIUM SULPHATE

Long-term exposure limit (8-hour TWA): 4 mg/m³ resp.dust

PORTLAND CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

WEL = Workplace Exposure Limit.

PORTLAND CEMENT (CAS: 65997-15-1)

DNEL

A derived no-effect level (DNEL) of 1 mg/m3 (as respirable dust) over an hour shift has been set

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Eye/face protection

Hand protection

Use mechanical ventilation if there is a risk of handling causing formation of airborne dust.

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Dust-resistant, chemical splash goggles.

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

ARC POT-CEM HIGH STRENGTH RAPID MORTAR

Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.	
Hygiene measures	Provide eyewash station. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.	
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Wear a suitable dust mask.	
SECTION 9: Physical and che	emical properties	
9.1. Information on basic phys	sical and chemical properties	
Appearance	Dusty powder.	
Relative density	1.6-2.0 @ @ 20°C	
9.2. Other information		
SECTION 10: Stability and re	activity	
10.1. Reactivity		
10.2. Chemical stability		
Stability	Stable at normal ambient temperatures and when used as recommended.	
10.3. Possibility of hazardous	reactions	
10.4. Conditions to avoid		
10.5. Incompatible materials		
Materials to avoid	Strong acids. Strong alkalis.	
10.6. Hazardous decompositi	on products	
SECTION 11: Toxicological information		
SECTION 11: Toxicological in		
SECTION 11: Toxicological ir 11.1. Information on toxicolog		
11.1. Information on toxicolog	ical effects	
11.1. Information on toxicolog	ical effects May cause damage to mucous membranes in nose, throat, lungs and bronchial system.	
11.1. Information on toxicolog	iical effects May cause damage to mucous membranes in nose, throat, lungs and bronchial system. May cause discomfort if swallowed.	
11.1. Information on toxicolog Inhalation Ingestion Skin contact	iical effects May cause damage to mucous membranes in nose, throat, lungs and bronchial system. May cause discomfort if swallowed. Prolonged contact with moist or wet product may cause burns. Risk of serious damage to eyes.	
11.1. Information on toxicolog Inhalation Ingestion Skin contact Eye contact	iical effects May cause damage to mucous membranes in nose, throat, lungs and bronchial system. May cause discomfort if swallowed. Prolonged contact with moist or wet product may cause burns. Risk of serious damage to eyes.	
11.1. Information on toxicolog Inhalation Ingestion Skin contact Eye contact SECTION 12: Ecological infor	ical effects May cause damage to mucous membranes in nose, throat, lungs and bronchial system. May cause discomfort if swallowed. Prolonged contact with moist or wet product may cause burns. Risk of serious damage to eyes. mation The product components are not classified as environmentally hazardous. However, large or	
11.1. Information on toxicolog Inhalation Ingestion Skin contact Eye contact SECTION 12: Ecological infor Ecotoxicity	ical effects May cause damage to mucous membranes in nose, throat, lungs and bronchial system. May cause discomfort if swallowed. Prolonged contact with moist or wet product may cause burns. Risk of serious damage to eyes. Imation The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.	
11.1. Information on toxicolog Inhalation Ingestion Skin contact Eye contact SECTION 12: Ecological infor Ecotoxicity 12.1. Toxicity 12.2. Persistence and degrad 12.3. Bioaccumulative potential	jical effects May cause damage to mucous membranes in nose, throat, lungs and bronchial system. May cause discomfort if swallowed. Prolonged contact with moist or wet product may cause burns. Risk of serious damage to eyes. mation The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment. ability	
11.1. Information on toxicolog Inhalation Ingestion Skin contact Eye contact SECTION 12: Ecological infor Ecotoxicity 12.1. Toxicity 12.2. Persistence and degrad 12.3. Bioaccumulative potenti 12.4. Mobility in soil	jical effects May cause damage to mucous membranes in nose, throat, lungs and bronchial system. May cause discomfort if swallowed. Prolonged contact with moist or wet product may cause burns. Risk of serious damage to eyes. mation The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment. ability al	
11.1. Information on toxicolog Inhalation Ingestion Skin contact Eye contact SECTION 12: Ecological infor Ecotoxicity 12.1. Toxicity 12.2. Persistence and degrad 12.3. Bioaccumulative potenti 12.4. Mobility in soil 12.5. Results of PBT and vPv	jical effects May cause damage to mucous membranes in nose, throat, lungs and bronchial system. May cause discomfort if swallowed. Prolonged contact with moist or wet product may cause burns. Risk of serious damage to eyes. mation The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment. ability al	
11.1. Information on toxicolog Inhalation Ingestion Skin contact Eye contact SECTION 12: Ecological infor Ecotoxicity 12.1. Toxicity 12.2. Persistence and degrad 12.3. Bioaccumulative potenti 12.4. Mobility in soil	jical effects May cause damage to mucous membranes in nose, throat, lungs and bronchial system. May cause discomfort if swallowed. Prolonged contact with moist or wet product may cause burns. Risk of serious damage to eyes. mation The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment. ability al B assessment	

ARC POT-CEM HIGH STRENGTH RAPID MORTAR

General information	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.	
SECTION 14: Transport in	formation	
General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).	
14.1. UN number		
14.2. UN proper shipping r	name	
14.3. Transport hazard cla	iss(es)	
14.4. Packing group		
14.5. Environmental hazar	ds	
14.6. Special precautions	for user	
14.7. Transport in bulk acc	cording to Annex II of MARPOL and the IBC Code	
SECTION 15: Regulatory	information	
15.1. Safety, health and er	nvironmental regulations/legislation specific for the substance or mixture	
National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).	
EU legislation	Dangerous Substances Directive 67/548/EEC.	
	Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18	
	December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of	
	Chemicals (REACH) (as amended).	
Guidance	Workplace Exposure Limits EH40.	
	Safety Data Sheets for Substances and Preparations.	
	Approved Classification and Labelling Guide (Sixth edition) L131.	
15.2. Chemical safety assessment		
SECTION 16: Other information		

General information	If further information on training is required contact Arc Building Products
Revision date	15/03/2022
Revision	1
Supersedes date	
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.

0

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.