

Colas Bitukold Rapid Set Joint Sealer Spray

Description:

RS Bitukold is a rapid setting, cold applied thixotropic bitumen emulsion designed for sealing vertical joints. The cationic formulation of RS Bitukold ensures a rapid set even in cold, damp conditions, with an initial cure taking place within 15 minutes. RS Bitukold is mainly used for the protection of new joints in freshly laid asphalt or macadam.

Where to use:

Transverse and longitudinal vertical joints, Trench reinstatements, Patch repairs
Drain or manhole frames, Kerb channels

Application:

Ensure that the surface is clean and free from loose materials, oil, grease, standing water and weeds. Shake can vigorously before use. Turn can upside down and apply RS Bitukold Spray in even strokes with nozzle 200-300mm away from the surface to be treated. Ensure complete coverage. After use spray briefly with can in upright position to clear nozzle.

Coverage:

The coverage rate for RS Bitukold Spray should be 0.7 – 1.5 kg/m², depending on the texture and porosity of the surface.

Packaging:

Colas Rapid Set Bitukold Spray is supplied in 600ml aerosol cans

Caution: pressurised container, protect from sunlight

Do not pierce or burn even after use

Do not expose to temperatures exceeding 50°C

Do not spray on a naked flame or any incandescent material

Keep out of reach of children

Store in an upright position

Certification:

RS Bitukold Spray complies with BS 594987: Clause 6.8 Joints, vertical face coating.