

PRODUCT OVERVIEW

O'Brien Cement Post Mix is a simple to use rapid setting concrete mix for fixing posts in the ground. It is pre-mixed and blended and contains cement, dried aggregates and admixtures. The cement used is O'Brien Cement manufactured in Ireland and conforms to I.S EN 197-1 2011.

Applications

Metal Posts Wooden Posts Plastic Posts Concrete Posts

INSTRUCTIONS FOR USE

- Insert the post centrally and support it vertically.
- Add water until hole is 1/3 to 1/2 full.
- Allow 3 to 4 liters of water for each bag of Post Mix used
- Carefully add Post Mix, filling the hole until no water is visible
- Sprinkle the top surface with water to wet any remaining dry powder.
- Tamp the surface to eliminate air bubbles.
- Check position of post and adjust / support, as necessary.
- Post Mix will set within 5 -10 minutes.





USAGE RATES

POST SIZE	HOLE SIZE (WIDTH& DEPTH	NO. OF BAGS
75mm SQUARE (3")	200mm (8") X 450mm (18")	1 BAG
	200mm (8") X 600mm (24")	1 BAG
	200mm (8") X 750mm (30")	1 BAG
	250mm (10") X 450mm (18")	1 - 2 BAGS
	250mm (10") X 600mm (24")	1 - 2 BAGS
100mm SQUARE (4")	250mm (10") X 450mm (18")	1 - 2 BAGS
	250mm (10") X 600mm (24")	1 - 2 BAGS
	250mm (10") X 750mm (30")	1 - 2 BAGS
	300mm (12") X 450mm (18")	1 - 2 BAGS
	300mm (12") X 600mm (24")	2 BAGS
	300mm (12") X 750mm (30")	2 - 3 BAGS

QUALITY STANDARDS



First Quality Standard


NSAI Certification creates, maintains and promotes accredited certification of our products, services and organisations for compliance with recognised standards



Second Quality Standard

We take responsibility for the compliance of a product with all applicable European health, safety, performance and environmental requirements.

PRODUCT CERTIFICATIONS



HEALTH AND SAFETY

- This product contains cement.
- Keep out of reach of children.
- Wear protection gloves, eye protection, face protection
- If in eyes rinse continuously with water for several minutes and immediately call for medical assistance
- If on skin wash with plenty of soap and water. Skin contact with wet cement or wet Mortar, may cause irritation, dermatitis or burns
- Avoid Breathing dust, if inhaled remove casualty to fresh air and keep at rest in a position comfortable for breathing
- Dispose of contents/container to an appropriate waste or recycling point.

DANGER

- H318 Causes serious eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

PRODUCT DATA AND **SUPPORT**

Monthly test data, and technical assistance is available on request. Further Information on this product and the full range of O'Brien Cement products can be obtained by contacting +353 (0)56 777 1111 or visit our website obriencement.ie/ obriencement.co.uk

